

ADVANCED SQL DDL

CS121: Relational Databases
Fall 2018 – Lecture 10

Advanced SQL DDL

2

- Last time, covered stored procedures and user-defined functions (UDFs)
 - Relatively simple but powerful mechanism for extending capabilities of a database
 - Most databases support these features (in different ways, of course...)
- Today, will cover three more advanced features of SQL data definition
 - Triggers
 - Materialized views (briefly)
 - Security constraints in databases

Triggers

3

- Triggers are procedural statements executed automatically when a database is modified
 - Usually specified in procedural SQL language, but other languages are frequently supported
- Example: an audit log for bank accounts
 - Every time a balance is changed, a trigger can update an “audit log” table, storing details of the change
 - e.g. old value, new value, who changed the balance, and why
- Why not have applications update the log directly?
 - Could easily forget to update audit log for some updates!
 - Or, a malicious developer might leave a back-door in an application, allowing them to perform unaudited operations

Triggers (2)

4

- If the database handles audit-log updates automatically and independently:
 - Application code doesn't become more complex by introducing audit functionality
 - Audit log will be a more trustworthy record of modifications to bank account records
- Triggers are used for many other purposes, such as:
 - Preventing invalid changes to table data
 - Automatically updating timestamp values, derived attributes, etc.
 - Executing business rules when data changes in specific ways
 - e.g. place an order for more parts when current inventory dips below a specific value
 - Replicating changes to another table, or even another database

Trigger Mechanism

5

- DB trigger mechanism must keep track of two things:
- When is the trigger actually executed?
 - The event that causes the trigger to be considered
 - The condition that must be satisfied before the trigger will execute
 - (Not every database requires a condition on triggers...)
- What does the trigger do when it's executed?
 - The actions performed when the trigger executes
- Called the event-condition-action model for triggers

When Triggers Execute

6

- Databases usually support triggering on inserts, updates, and deletes
- Can't trigger on selects
 - Implication: Can't use triggers to audit or prevent read-accesses to a database (bummer)
- Commercial databases also support triggering on many other operations
 - Data-definition operations (create/alter/drop table, etc.)
 - Login/logout of specific users
 - Database startup, shutdown, errors, etc.
- For simplicity, will limit discussion to DML triggers only

When Triggers Execute

7

- Can typically execute the trigger before or after the triggering DML event
 - Usually, DDL/user/database triggering events only run the trigger *after* the event (pretty obvious)
 - “Before” triggers can abort the DML operation, if necessary
- Some DBs also support “instead of” triggers
 - Execute trigger instead of performing the triggering operation
- Triggers are row-level triggers or statement-level triggers
 - A row-level trigger is executed for every single row that is modified by the statement
 - (...as long as the row satisfies the trigger condition, if specified...)
 - A statement-level trigger is executed once for the entire statement

Trigger Data

8

- Row-level triggers can access the old and new version of the row data, when available:
 - Insert triggers only get the new row data
 - Update triggers get both the old and new row data
 - Delete triggers only get the old row data
- Triggers can also access and modify other tables
 - e.g. to look up or record values during execution

Trigger Syntax

9

- SQL:1999 specifies a syntax for triggers
 - Discussed in the textbook, section 5.3
- Again, wide variation from vendor to vendor
 - Oracle and DB2 are similar to SQL99, but not identical
 - (triggers always seem to involve vendor-specific features)
 - SQLServer, Postgres, MySQL all have different features
 - Constraints on what triggers can do also vary widely from vendor to vendor
- Will focus on MySQL trigger syntax, functionality

Trigger Example: Bank Overdrafts

10

- Want to handle overdrafts on bank accounts
- If an update causes a balance to go negative:
 - Create a new loan with same ID as the account number
 - Set the loan balance to the negative account balance
 - (...the account balance went negative...)
 - Need to update **borrower** table as well!
- Needs to be a row-level trigger, executed before or after updates to the **account** table
 - If database supports trigger conditions, only trigger on updates when account balance < 0

SQL99/Oracle Trigger Syntax

11

- Book uses SQL:1999 syntax, similar to Oracle/DB2

```
CREATE TRIGGER trg_overdraft AFTER UPDATE ON account
REFERENCING NEW ROW AS nrow
FOR EACH ROW WHEN nrow.balance < 0
BEGIN ATOMIC
    INSERT INTO loan VALUES (nrow.account_number,
                                nrow.branch_name,
                                -nrow.balance);

    INSERT INTO borrower
        (SELECT customer_name, account_number
         FROM depositor AS d
         WHERE nrow.account_number = d.account_number);

    UPDATE account AS a SET balance = 0
        WHERE a.account_number = nrow.account_number;
END
```

MySQL Trigger Syntax

12

- MySQL has more limited trigger capabilities
 - Trigger execution is only governed by events, not conditions
 - Workaround: Enforce the condition within the trigger body
 - Old and new rows have fixed names: **OLD, NEW**
- Change the overdraft example slightly:
 - Also apply an overdraft fee! “*Kick ‘em while they’re down!*”
- What if the account is already overdrawn?
 - Loan table will already have a record for overdrawn account...
 - Borrower table will already have a record for the loan, too!
 - Previous version of trigger would cause duplicate key error!

MySQL INSERT Enhancements

13

- MySQL has several enhancement to the **INSERT** command
 - (Most databases provide similar capabilities)
- Try to insert a row, but if key attributes are same as another row, simply don't perform the insert:
INSERT IGNORE INTO *tbl* ...;
- Try to insert a row, but if key attributes are same as another row, update the existing row:
**INSERT INTO *tbl* ... ON DUPLICATE KEY
UPDATE *attr1* = *value1*, ...;**
- Try to insert a row, but if key attributes are same as another row, replace the old row with the new row
 - If key is not same as another row, perform a normal **INSERT**
REPLACE INTO *tbl* ...;

MySQL Trigger Syntax (2)

14

```
CREATE TRIGGER trg_overdraft BEFORE UPDATE ON account FOR EACH ROW
BEGIN
    DECLARE overdraft_fee NUMERIC(12, 2) DEFAULT 30;
    DECLARE overdraft_amt NUMERIC(12, 2);

    -- If an overdraft occurred then handle by creating/updating a loan.
    IF NEW.balance < 0 THEN
        -- Remember that NEW.balance is negative.
        SET overdraft_amt = overdraft_fee - NEW.balance;

        INSERT INTO loan (loan_number, branch_name, amount)
            VALUES (NEW.account_number, NEW.branch_name, overdraft_amt)
        ON DUPLICATE KEY UPDATE amount = amount + overdraft_amt;

        INSERT IGNORE INTO borrower (customer_name, loan_number)
            SELECT customer_name, account_number FROM depositor
            WHERE depositor.account_number = NEW.account_number;

        SET NEW.balance = 0;
    END IF;
END;
```

Trigger Pitfalls

15

- Triggers may *or may not* execute when you expect...
 - e.g. MySQL insert-triggers fire when data is bulk-loaded into the DB from a backup file
 - Databases usually allow you to temporarily disable triggers
 - e.g. truncating a table usually does not fire delete-triggers
- If a trigger for a commonly performed task runs slowly, it will kill DB performance
- If a trigger has a bug in it, it may abort changes to tables at unexpected times
 - The *actual* cause of the issue may be difficult to discern
- Triggers can write to other tables, which may also have triggers on them...
 - Not hard to create an infinite chain of triggering events

Alternatives to Triggers

16

- Triggers can be used to implement *many* complex tasks
- Example: Can implement referential integrity with triggers!
 - On all inserts and updates to referencing table, ensure that foreign-key column value appears in referenced table
 - If not, abort the operation!
 - On all updates and deletes to referenced table, ensure that value doesn't appear in referencing table
 - If it does, can abort the operation, or cascade changes to the referencing relation, etc.
- This is definitely slower than the standard mechanism ☺

Alternatives to Triggers (2)

17

- Can you use stored procedures instead?
 - Stored procedures usually have fewer limitations than triggers
 - Stored procs can take more detailed arguments, return values to indicate success/failure, have out-params, etc.
 - Can perform more sophisticated transaction processing
 - Trigger support is also very vendor-specific, so either implementation choice will have this limitation
- Typically, triggers are used in very limited ways
 - Update “row version” or “last modified timestamp” values in modified rows
 - Simple operations that don’t require a great deal of logic
 - Database replication (sometimes)

Triggers and Summary Tables

18

- Triggers are sometimes used to compute summary results when detail records are changed
- Example: a table of branch summary values
 - e.g. (branch_name, total_balances, total_loans)
- Motivation:
 - If these values are used frequently in queries, want to avoid overhead of recomputing them all the time
- Idea: update this summary table with triggers
 - Anytime changes are made to account or loan, update the summary table based on the changes

Materialized Views

19

- Some databases provide materialized views, which implement such functionality
- Simple views usually treated as named SQL queries
 - i.e. a derived relation with the specified definition
- When a query refers to a simple view, database substitutes view's definition directly into the query
 - Benefit: allows optimization of the entire query
 - Drawback: if many queries reference a simple view, the same values will be computed again and again...

Materialized Views (2)

20

- Materialized views actually create a new table, populated by the results of the view definition
 - Queries can use values in the materialized view over and over, without recomputing
 - Database can perform optimized lookups against the materialized view, e.g. by using indexes
- Just one little problem:
 - What if the tables referenced by the view change?
 - Need to recompute contents of the materialized view!
 - Called view maintenance

Materialized View Maintenance

21

- If a database doesn't support materialized views:
 - Can perform view maintenance with triggers on the referenced tables
 - A very manual approach, but definitely an option for databases that don't support materialized views
 - e.g. Postgres, MySQL
- Databases with materialized views will perform view maintenance automatically
 - ...much simpler than creating a bunch of triggers!
 - Typically provide many options, such as:
 - Immediate view maintenance – update contents after any change
 - Deferred view maintenance – update view on a periodic schedule

Materialized View Maintenance (2)

22

- A simple approach for updating materialized views:
 - Recompute entire view from scratch after every change!
 - Very expensive approach, especially if backing tables are changed frequently
- A better approach: incremental view maintenance
 - Using the view definition and the specific data changes applied to the backing tables, only update those parts of the view that are actually affected
- Again, DBs with materialized views will do this for you
- Can also do incremental view maintenance manually with triggers, but it can be complicated...

Authentication and Authorization

23

- Security systems must provide two major features
- Authentication (aka “A1”, “AuthN”, “Au”):
 - “I am who I say I am.”
- Authorization (aka “A2”, “AuthZ”, “Az”):
 - “I am allowed to do what I want to do.”
- Each component is useless without the other

User Authorization

24

- SQL databases perform authentication of users
 - Must specify username and password when connecting
 - Most DBMSes provide secure connections (e.g. SSL), etc.
- SQL provides an authorization mechanism for various operations
 - Different operations require different privileges in the database
 - Users can be granted privileges to perform necessary operations
 - Privileges can also be revoked, to limit available user operations

Basic SQL Privileges

25

- Most fundamental set of privileges:
 - **SELECT, INSERT, UPDATE, DELETE**
 - Allows (or disallows) user to perform specified action
 - User is granted access to perform specified operations on particular relations
- Simple syntax:
`GRANT SELECT ON account TO banker;`
 - User “banker” is allowed to issue queries against the *account* relation

Granting Privileges

26

- Can grant multiple privileges to multiple users

```
GRANT SELECT, UPDATE ON account  
    TO banker, manager;
```

```
GRANT INSERT, DELETE ON account  
    TO manager;
```

- Bankers can view and modify account balances
- Only managers can create or remove accounts
- Must specify each table individually

All Users, All Privileges

27

- Can specify **PUBLIC** to grant privileges to all users
 - Also includes users added to DBMS in future

```
GRANT SELECT ON promotions TO PUBLIC;
```
- Can specify **ALL PRIVILEGES** to grant all privileges to a user

```
GRANT ALL PRIVILEGES ON account  
TO admin_lackey;
```

Column-Level Privileges

28

- For **INSERT** and **UPDATE** privileges, can optionally constrain to specific *columns* of relations
 - **UPDATE**: can only update specified columns
 - **INSERT**: can only insert into specified columns
- Example: *employee* relation
 - Employees can only modify their contact info
 - Allow HR to manipulate *all* aspects of employees

```
GRANT UPDATE (home_phone, email) ON employee  
TO emp_user;  
  
GRANT INSERT, UPDATE ON employee TO hr_user;
```

Revoking Privileges

29

- Can revoke privileges just as easily:
`REVOKE priv1, ... ON relation
FROM user1, ...;`
 - Can specify a list of privileges, and a list of users
- With **INSERT** and **UPDATE**, can also revoke privileges on individual columns

Privileges and Views

30

- Users can be granted privileges on views
 - May differ from privileges on underlying tables
- When accessing a view:
 - Privileges on the view are checked, not the privileges on underlying tables
- Example: *employee* relation
 - Only HR can view all employee data
 - Employees can only view contact details

Example View Privileges

31

- SQL commands:

```
-- Start by disallowing all access to employee  
REVOKE ALL PRIVILEGES ON employee TO PUBLIC;
```

```
-- Only allow hr_user to access employee relation  
GRANT ALL PRIVILEGES ON employee TO hr_user;
```

```
-- View for "normal" employees to access  
CREATE VIEW directory AS  
    SELECT emp_name, email, office_phone  
    FROM employee;  
GRANT SELECT ON directory TO emp_user;
```

- When employees issue queries against *directory*, DB only checks *directory* privileges

View Processing

32

- As stated before, databases usually treat views as named SQL queries
 - ▣ Database substitutes view's definition directly into queries that reference the view
- SQL engine performs authorization **before** this process occurs
 - ▣ DB verifies access permissions on referenced views, and then substitutes view definitions into the query plan
 - ▣ Allows DB to support different access constraints on views, vs. their underlying tables

Other Privileges

33

- Many other privileges in SQL
 - **EXECUTE** grants privilege to execute a function or stored procedure
 - **CREATE** grants privilege to create tables, views, other schema objects
 - **REFERENCES** grants privilege to create foreign key or **CHECK** constraints
 - Most DBMSes provide several others, too
 - PostgreSQL has 11 permissions; MySQL has 27
 - Oracle has nearly 200 different permissions!

REFERENCES Privilege

34

- Foreign key constraints limit what users can do
 - Rows in referencing relation limit update and delete operations in referenced relation
 - A user adding a foreign key constraint can disallow these operations for all users!
- Must have the **REFERENCES** privilege to create foreign keys
- **REFERENCES** requires both a relation and some attributes to be specified
 - May create foreign keys involving those attributes

Passing On Privileges

35

- Users can't automatically grant their own privileges to other users

- Must explicitly allow this:

```
GRANT SELECT ON directory TO emp_user  
    WITH GRANT OPTION;
```

- WITH GRANT OPTION clause allows privileges to be passed on
- Can lead to confusing situations:
 - If **alex** grants a privilege to **bob**, then **alex** has that privilege revoked, should it affect **bob**?
 - If **alex** and **bob** both grant a privilege to **carl**, then **alex** revokes that privilege, does **carl** still have the privilege?
- Typically, databases implement simple solutions to these kinds of problems

Authorization Notes

36

- SQL authorization mechanism is very rich
- Still has a number of shortcomings
 - Can't grant/revoke privileges on per-tuple basis
 - e.g. "I can see only the rows in the *account* relation corresponding only to my bank accounts."
 - (If there were **SELECT** triggers, we could implement this...)
 - (Or, you could emulate this with table-returning functions...)
 - Significant variations in security models implemented by various databases

Authorization Notes (2)

37

- Most applications don't rely heavily on DB authorization
 - Application can implement a broad range of authorization schemes, but implementation complexity increases
 - Web applications are primary example of this
 - Database access layer typically has only one user, with full access and modification privileges
- Application performs authentication/authorization itself
 - Access-checks are sprinkled throughout application code; easy to introduce security holes! (e.g. PHP applications)
 - App-servers with declarative security specifications greatly mitigate this problem (e.g. JavaEE platform security)

Authorization Notes (3)

38

- Best to employ SQL auth mechanism in *some way...*
 - Declarative security specifications
 - Database simply won't allow access to privileged data, or unauthorized changes to schema
- For large, important database apps, definitely want to explore using SQL authorization features
 - At the least, create a DBMS user for each user-role that application supports
 - An “admin” user for administrators in the application, with fewer restrictions
 - A very restricted “common user” for end-users
 - Greatly reduces the dangers of SQL-based attacks

Next Time

39

- Last major topic for SQL data definition: indexes
 - Used to facilitate *much* faster database lookups
- Will also briefly discuss DB storage mechanisms, and how this affects query performance